



EPE151

Electric Pallet Truck 1.5T

- Robust
- Simple
- No Trouble

EP EQUIPMENT CO.,LTD
www.buy-imow.com



Scan and Enter iMOW Website



EP EQUIPMENT CO.,LTD

NO.121 Yonghua Street, Shiqiao Road, Xia Cheng Qu , Hangzhou, China 86-571-28035665

86-571-28035656/28878695

www.buy-imow.com

info@ep-ep.com

www.ep-ep.com

PRODUCT FEATURES

■ Robust and durable

All-metal Protection, Better strength;
Using Mechanical spring to replace air spring
in handle movement, which lengthen the service
life.

■ Simple

Open the front cover plate to realize easy
maintenance.

■ No Trouble

Built-in charger and maintenance free AGM
Battery.



ANGLE VIEW



*Pictures shown are for reference only. Actual product may vary due to product enhancement.

PRODUCT PARAMETERS

Distinguishing mark			
1.1	Manufacturer		EP
1.2	Model designation		EPE151
1.3	Drive unit		Electrics
1.4	Operator type		pedestrian
1.5	rated capacity	Q	kg
1.6	Load center distance	c	mm
1.8	Load distance	x	mm
1.9	Wheelbase	y	mm
Weight			
2.1	Service weight (include battery)		kg
2.2	Axle loading, laden driving side/loading side		kg
2.3	Axle loading, unladen driving side/loading side		kg
Types,Chassis			
3.1	Tyre type driving wheels/loading wheels		PU/ PU
3.2	Tyre size, driving wheels (diameter×width)		mm
3.3	Tyre size, loading wheels (diameter×width)		mm
3.4	Tyre size, caster wheels (diameter×width)		mm
3.5	Wheels, number driving, caster/loading (x=drive wheels)		mm
3.6	Track width, front,driving side	b ₁₀	mm
3.7	Track width,rear,loading side	b ₁₁	mm
Dimensions			
4.4	Lift height	h ₃	mm
4.9	Height drawbar in driving position min./max.	h ₁₄	mm
4.15	Lowered height	h ₁₃	mm
4.19	Overall length	l ₁	mm
4.20	Length to face of forks	l ₂	mm
4.21	Overall width	b ₁ / b ₂	mm
4.22	Fork dimensions	s/ e/ l	mm
4.25	Outside width of the forks	b ₅	mm
4.32	Ground clearance, center of wheelbase	m ₂	mm
4.34.1	Aisle width for pallets 1000 × 1200 crossways	Ast	mm
4.34.2	Aisle width for pallets 800 × 1200 lengthways	Ast	mm
4.35	Turning radius	Wa	mm
Performance data			
5.1	Travel speed, laden/ unladen	km/ h	km/h
5.2	Lifting speed, laden/ unladen		m/ s
5.3	Lowering speed, laden/ unladen		m/ s
5.8	Max. gradeability, laden/unladen		%
5.10	Service brake type		Electromagnetic
Electric-engine			
6.1	Drive motor rating S2 60 min		kW
6.2	Lift motor rating at S3 15%		kW
6.3	The maximum allowed size battery		mm
6.4	Battery voltage/nominal capacity K20		V/ Ah
6.5	Battery weight		kg
Addition data			
8.1	Type of drive control		DC
10.5	Steering type		Mechanical
10.7	Sound pressure level at the driver's ear		dB (A)

LINE GRAPH

